HS-25/25A Rocking Shaker

Shaker & Rocker

Introduction

The Rocking Shaker is a benchtop oscillating shaker suitable for use in greenhouses and incubators. It is widely used in various laboratory applications, including electrophoresis gel fixation, Coomassie blue staining, decolourisation, silver nitrate staining, dye staining and development.

Feature

1. Features a stainless steel and natural rubber platform that is resistant to acids and alkalis, deformation and spills, and is easy to clean.
2. Displays operating speed and remaining time in real time.
3. Equipped with articulated rotating bearings for secure, wear-resistant and long-term operation.
4. Compact design that saves laboratory space.
5. Features a simple, user-friendly design.
6. Uses a stepper motor for quiet operation.



HS-25A

Accessories



Flat platform with non-slip rubber mat



Ddouble deck flat platform with non-slip rubber mat

Parameter

Model	HS-25	HS-25A
Speed Range	5~80rpm	5~80rpm
Swing Cycloid	25mm (up and down) / 10°	25mm (up and down) / 10°
Time Range	1min~99h59min	1min~99h59min
Max. Load	5.0kgs (single-deck platform)	5.0kgs (double-deck platform)
Platform Dimension	L.280 x W.228mm	L.280 x W.228mm
Voltage	AC 100~230V, 50/60 Hz	AC 100~230V, 50/60 Hz
Power	50W	50W
Fuse	250V, 1A, Φ5x20	250V, 1A, Φ5x20
Dimension	W.284 x D.264 x H.134mm	W.284 x D.264 x H.248mm
Net Weight	5.2kgs	6.0kgs



HS-25